

AMENDMENT TO THE CLAIMS

1. (currently amended) A cap assembly that can be associated with a container storing a primary material, the cap assembly comprising:

a lid fixed on a top of the container and having an exhausting portion projected upward;

a cap main body detachably coupled to the exhausting portion of the lid and having a storage tube extending downward to define a storage chamber for storing a secondary material;

an inner cap body detachably coupled to the storage tube; and

wherein the exhausting portion tightly contacts an outer surface of the storage tube, further including a plurality of exhausting pieces which extend radially inward and into an exhausting space of the container and include bending portions for selectively separating the inner cap body ~~for~~from the storage tube.

2. (cancelled)

3. (previously presented) The cap assembly of claim 1, wherein the bending portion is projected inward.

4. (original) The cap assembly of claim 1, wherein a top surface of the container and a lower surface of the lid are provided with respective attaching surfaces attached to each other.

5. (cancelled)

6. (cancelled)

7. (currently amended) A cap assembly that can be associated with a container storing a primary material, the cap assembly comprising:

a lid fixed on a top of the container and having a falling space and an inner cap body

extending from the falling space;
a cap main body detachably coupled to an exhausting portion of the lid and having a storage tube extending downward to define a storage chamber for storing a secondary material, a lower end of the storage chamber being closed by the inner cap body;
a cap body detachably coupled to the exhausting portion;
a storage member functioning as a straw, the storage member being slidably inserted in the cap body to define a storage chamber storing a secondary material and being closed by the inner cap body wherein a lower end of the storage chamber is opened when the storage member slides in a direction away from the inner cap body and the inner cap body remains coupled to the falling space; and
an outer cap body detachably coupled to the exhausting portion, the storage member being coupled in the outer cap body;
wherein removal of the outer cap body causes the storage member to slide in the direction away from the inner cap body and movement of the storage member is limited by a hooking step on the exhausting portion which abuts~~and~~ a stopper on the storage member.

8. (original) The cap assembly of claim 7, wherein the cap body is provided at an inner portion with a hooking step and the storage member is provided with a stopper that is to be hooked on the hooking step.

9. (previously presented) The cap assembly of claim 7, wherein the storage member has a portion detachably coupled on an inner surface of the outer cap body.

10. (cancelled)

11. (cancelled)

12. (cancelled)

13. (cancelled)

14. (cancelled)

15. (currently amended) A cap assembly that can be associated with a container storing a primary material, the cap assembly comprising:

 a lid fixed on a top of the container and provided with an exhausting portion and a plurality of exhausting pieces extending from a lower portion of the exhausting portion;

 a cap body detachably coupled to the exhausting portion and having a storage tube extending downward to define a storage chamber for storing a secondary material;
 and

 an inner cap detachably coupled to the lower portion of the storage tube; and

 wherein the exhausting pieces are to coupled to the lid and extend radially inward from the lid and into the container and which contact the edge of the inner cap inserted in the lower end of the storage tube, the exhausting pieces configured to detach the inner cap from the storage tube.

16. (cancelled)

17. (previously presented) The cap assembly of claim 15, wherein the exhausting pieces have a bending portion inserted between an upper end of the inner cap body and a lower end of the storage tube.